

DAVAN FLOWTEK



По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Россия (495)268-04-70

Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Казахстан (7172)727-132

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Эл. почта dya@nt-rt.ru || Сайт: <https://davanflowtek.nt-rt.ru/>

法兰系列 FLANGE VALVE

ML-1404 Flange Brass Gate Valve 法兰黄铜闸阀



DN	Size	L	H	D	D1	n-Ød
125	5"	162	400	210	240	8-Ø18
150	6"	184	440	240	240	8-Ø23
200	8"	234	550	295	300	12-Ø23
250	10"	253	610	355	400	12-Ø25
300	12"	287	670	410	400	12-Ø23

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1407 Flange Brass Stop Valve 法兰黄铜截止阀



DN	Size	L	H	D	D1	n-Ød
15	1/2"	79	81	65	78	4-Ø14
20	3/4"	89	85	75	78	4-Ø14
25	1"	93	98	85	78	4-Ø14
32	1 1/4"	110	125	100	108	4-Ø18
40	1 1/2"	132	136	110	108	4-Ø18
50	2"	172	173	125	143	4-Ø18
65	2 1/2"	198	190	145	143	8-Ø18
80	3"	249	276	160	200	8-Ø18
100	4"	276	290	180	240	8-Ø18

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1405 Flange Brass Stop Valve 法兰黄铜截止阀



DN	Size	L	H	D	D1	n-Ød
15	1/2"	79	81	65	78	4-Ø14
20	3/4"	89	85	75	78	4-Ø14
25	1"	93	98	85	78	4-Ø14
32	1 1/4"	110	125	100	108	4-Ø18
40	1 1/2"	132	136	110	108	4-Ø18
50	2"	172	173	125	143	4-Ø18
65	2 1/2"	198	190	145	143	8-Ø18
80	3"	249	276	160	200	8-Ø18
100	4"	276	290	180	240	8-Ø18
125	5"	337	315	210	240	8-Ø18
150	6"	355	380	240	300	8-Ø23

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1408 Flange Brass Filter 法兰黄铜过滤器



DN	Size	L	H	D	n-Ød
32	1 1/4"	152	95	100	4-Ø18
40	1 1/2"	176	106	110	4-Ø18
50	2"	210	115	125	4-Ø18
65	2 1/2"	246	155	145	4-Ø18
80	3"	273	190	160	8-Ø18
100	4"	315	230	180	8-Ø18
125	5"	341	255	210	8-Ø18
150	6"	402	280	240	8-Ø23

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1406 Bellows Brass Stop Valve 波纹管黄铜截止阀



DN	Size	L	H	D	D1	n-Ød
15	1/2"	79	81	65	78	4-Ø14
20	3/4"	89	85	75	78	4-Ø14
25	1"	93	98	85	78	4-Ø14
32	1 1/4"	110	125	100	108	4-Ø18
40	1 1/2"	132	136	110	108	4-Ø18
50	2"	172	173	125	143	4-Ø18
65	2 1/2"	198	190	145	143	8-Ø18
80	3"	249	276	160	200	8-Ø18
100	4"	276	290	180	240	8-Ø18

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1409 Flange Brass Check Valve 法兰黄铜止回阀



DN	Size	L	H	D	n-Ød
40	1 1/2"	132	75	110	4-Ø18
50	2"	144	80	125	4-Ø18
65	2 1/2"	163	90	145	4-Ø18
80	3"	187	105	160	8-Ø18
100	4"	210	115	180	8-Ø18
125	5"	237	130	210	8-Ø18
150	6"	267	160	240	8-Ø23

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228



优质黄铜
High Quality
Brass



成熟工艺
Mature
Technology



标准检测
Standard
Detection



超长使用
Extra Long
Use

青铜系列 BRONZE VALVE

ML-1501 Bronze Ball Valve 青铜球阀



DN	Size	L	H	D
15	1/2"	50.5	44.5	94
20	3/4"	56	51	94
25	1"	67	62	105
32	1 1/4"	91	72	138
40	1 1/2"	102	77	162
50	2"	116	82	170
65	2 1/2"			
80	3"			
100	4"			

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1505 Bronze Stop Valve 青铜截止阀



DN	Size	L	B	M	D	H
15	1/2"					
20	3/4"	68	19	14	63	86
25	1"	73	25	15	63	87
32	1 1/4"	89	32	18	70	125
40	1 1/2"					
50	2"					

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1502 Bronze Gate Valve 青铜闸阀



DN	Size	L	H	D
15	1/2"	50.5	44.5	94
20	3/4"	56	51	94
25	1"	67	62	105
32	1 1/4"	91	72	138
40	1 1/2"	102	77	162
50	2"	116	82	170
65	2 1/2"			
80	3"			
100	4"			

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1506 Bronze Stop Valve 青铜截止阀



DN	Size	L	B	M	D	H
15	1/2"	48	12	10	55	70
20	3/4"	53	14	11	60	71
25	1"	63	16	12	70	83
32	1 1/4"					
40	1 1/2"					
50	2"					

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1503 Bronze Gate Valve 青铜闸阀



DN	Size	L	H	D
15	1/2"	50.5	44.5	94
20	3/4"	56	51	94
25	1"	67	62	105
32	1 1/4"	91	72	138
40	1 1/2"	102	77	162
50	2"	116	82	170
65	2 1/2"			
80	3"			
100	4"			

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1507 Bronze Filter 青铜过滤器



DN	Size	L	B	H
15	1/2"	74	12	47
20	3/4"	86	16	57
25	1"	91	22	64
32	1 1/4"	118	28	79.5
40	1 1/2"	128	38.5	88.5
50	2"	151	47	103

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1504 Welded Bronze Gate Valve 焊接青铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	43	13	12	60	72.5
20	3/4"	49	17	16	65	78
25	1"	66	21	22	65	90
32	1 1/4"	75	27	24	80	110
40	1 1/2"	81	34	26.5	100	123
50	2"	92	45	31	125	142

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1508 Bronze Check Valve 青铜止回阀



DN	Size	L	B	H
15	1/2"	54	14	33
20	3/4"	63	18	39
25	1"	70	23.5	46
32	1 1/4"	81	28	51
40	1 1/2"	91	36	58
50	2"	109	45	66

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228



优质黄铜
High Quality
Brass



成熟工艺
Mature
Technology



国家标准
Standard
Detection



超长使用
Extra Long
Use

闸阀系列 GATE VALVE

ML-1001 Brass Gate Valve 黄铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	44	13	11.5	55	78
20	3/4"	49	19	14	60	85
25	1"	51	24	14	70	95
32	1 1/4"	59	30	15	70	115
40	1 1/2"	61	37	17	70	122
50	2"	70	47	17	85	155
65	2 1/2"					
80	3"					
100	4"					

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1005 Brass Gate Valve 黄铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	46	13.5	12.5	55	70
20	3/4"	50	17	14	55	73
25	1"	58	23	17	65	93
32	1 1/4"	63	29	17	70	105
40	1 1/2"	65	38	18	70	122
50	2"	73	47	19	90	147
65	2 1/2"	81	57	20	100	178
80	3"	86	71	21	110	200
100	4"	95	90	23	125	230

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1002 Brass Gate Valve 黄铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	43	13	13	55	73
20	3/4"	47	17	14	55	78
25	1"	50	21	14	60	85
32	1 1/4"	55	27	15	70	100
40	1 1/2"	60	34	16	70	119
50	2"	69	45	18	85	127
65	2 1/2"	87	56	25	100	165
80	3"	92	67	25	110	193
100	4"	108	90	28	125	233

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1006 Brass Gate Valve 黄铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	39	13	11	55	71
20	3/4"	44	19	11	55	82
25	1"	48	24	13	60	94
32	1 1/4"	59	28	16	70	105
40	1 1/2"	63	36	15	71	122
50	2"	72	47	20	85	140
65	2 1/2"	78	59	21	100	185
80	3"	90	71	22	110	200
100	4"	108	90	23	125	230

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1003 Brass Gate Valve 黄铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	40	13	11	55	68
20	3/4"	42	15	11.5	55	71
25	1"	48	19	12.5	60	77
32	1 1/4"	52	27	14	70	96
40	1 1/2"	57	32	15	71	108
50	2"	58	36	14	85	121
65	2 1/2"	81	60	19	100	179
80	3"	84	71	18	110	201
100	4"	96	88	21	125	243

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1007 Brass Gate Valve 黄铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	36	13	11	50	63
20	3/4"	39	15	11	55	64
25	1"	46	19	13	60	72
32	1 1/4"	48	27	12	70	90
40	1 1/2"	49	33	12	75	99
50	2"	54	42	13	90	122
65	2 1/2"	63	56	14	100	168
80	3"	65	70	13	110	185
100	4"	79	94	14	125	230

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1004 Brass Gate Valve 黄铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	39	13	11	55	72
20	3/4"	44	17	12.5	55	78
25	1"	51	21	13.5	60	83
32	1 1/4"	54	27	15	70	104
40	1 1/2"	57	34	15	70	115
50	2"	62	45	15	85	136
65	2 1/2"	78	59	21	110	185
80	3"	90	71	22	110	200
100	4"					

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1008 Brass Gate Valve 黄铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	37	13	10.2	50	65.5
20	3/4"	42	19	11	55	75.5
25	1"	48	24	13	60	90
32	1 1/4"	54	32	14.5	70	103
40	1 1/2"	58	37	15	80	119
50	2"	66	49	17	90	150
65	2 1/2"	70	51	18	100	160
80	3"	74	67	18	110	183
100	4"	82	87	19	125	218

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228



优质黄铜
High Quality
Brass



成熟工艺
Mature
Technology



标准检测
Standard
Detection



超长使用
Extra Long
Use

闸阀系列 GATE VALVE

ML-1009 Brass Gate Valve 黄铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	41	13	12.5	55	72.5
20	3/4"	44	18	12.5	55	80
25	1"	50	24	13	60	96
32	1 1/4"	56	30	15	70	111
40	1 1/2"	67.5	37	18	70	125
50	2"	71	45	20	85	142
65	2 1/2"	86	55	22	95	173
80	3"	84	70	17.5	110	202
100	4"	91	96	20	125	251

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1013 Brass Gate Valve 黄铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	39	13	11	55	73
20	3/4"	46	16.5	12.5	55	84
25	1"	51	24	13	60	95
32	1 1/4"	53	30	13	70	106
40	1 1/2"	60	37	16	70	113
50	2"	65	45	16	85	137
65	2 1/2"	77	60	19	100	176
80	3"	93	70	23	110	202
100	4"	100	87	24	125	241

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1010 Brass Gate Valve 黄铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	43	13	12	55	73
20	3/4"	47	18	14	55	83
25	1"	53.5	21	16	60	87
32	1 1/4"	60	30	16	70	106
40	1 1/2"	58	35	15.5	70	117
50	2"	69	45	19	85	142
65	2 1/2"	79	60	20	100	176
80	3"	92	70	24	110	196
100	4"	106	95	29	127	247

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1014 Brass Gate Valve 黄铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	39	13	11	55	73
20	3/4"	46	16.5	12.5	55	84
25	1"	51	24	13	60	95
32	1 1/4"	53	30	13	70	106
40	1 1/2"	60	37	16	70	113
50	2"	65	45	16	85	137
65	2 1/2"	77	60	19	100	175.5
80	3"	93	70	23	110	202
100	4"	100	87	24	125	241

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1011 Brass Gate Valve 黄铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	42	13	12.5	55	77
20	3/4"	44	19	11.5	55	82
25	1"	51	25	14	65	94
32	1 1/4"	58	31	16	70	115
40	1 1/2"	60	37	15.5	75	120
50	2"	69	48	17	85	150
65	2 1/2"	76	65	19	100	190
80	3"	87	65	20	110	195
100	4"	106	87	24	125	240

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1015 Brass Gate Valve 黄铜带锁闸阀



DN	Size	L	B	M	D	H
15	1/2"	42	13	13	62.5	
20	3/4"	50.5	17	15	67	
25	1"	51	21	14	76	
32	1 1/4"					
40	1 1/2"					
50	2"					
65	2 1/2"					
80	3"					
100	4"					

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1012 Brass Gate Valve 黄铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	36	13	9	60	71.5
20	3/4"	44	17	13	60	79
25	1"	55	21	14.5	65	91
32	1 1/4"	56	30.5	15	80	106
40	1 1/2"	56.5	32	15	95	127
50	2"	69.5	45	17	105	144
65	2 1/2"	84	59	20	115	196
80	3"	87	70	22	145	213
100	4"	112	87	25	145	240

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1016 Brass Gate Valve 黄铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	33	13	8	55	70
20	3/4"	42	17	12	60	79
25	1"	47	21	11	65	87
32	1 1/4"	55	27	14	80	110
40	1 1/2"	62.5	38	16	90	126
50	2"	69	45	16.5	100	146
65	2 1/2"	80	60	17	110	190
80	3"	83	70	15	130	210
100	4"	97	88	18	150	240

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228



优质黄铜
High Quality
Brass



成熟工艺
Mature
Technology



国家标准
Standard
Detection



超长使用
Extra Long
Use

闸阀系列 GATE VALVE

ML-1201 Brass Compressed Gate Valve 黄铜卡套闸阀



DN	Size	L	B	M	D	H
15	1/2"	62.6	13	13	60	79.5
20	3/4"	69	19	16	65	84.5
25	1"	80	21	17.5	65	93
32	1 1/4"	102	31	19	80	120.5
40	1 1/2"	106	37	27	100	141
50	2"	127	38	28	110	164
65	2 1/2"					
80	3"					
100	4"					

Technical Standard
 1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1301 Welded Brass Gate Valve 焊接黄铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	43	13	12	60	70
20	3/4"	49	17	16	65	75
25	1"	66	21	22	65	87
32	1 1/4"	75	27	24	80	106
40	1 1/2"	81	34	26.5	100	117
50	2"	92	45	31	110	138
65	2 1/2"					
80	3"					
100	4"					

Technical Standard
 1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1202 Brass Compressed Gate Valve 黄铜卡套闸阀



DN	Size	L	B	M	D	H
15	1/2"	63	13	14	50	67.4
20	3/4"	66	18	13	55	74
25	1"	75	24	15	60	80
32	1 1/4"					
40	1 1/2"					
50	2"					
65	2 1/2"					
80	3"					
100	4"					

Technical Standard
 1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1302 Welded Brass Gate Valve 焊接黄铜闸阀



DN	Size	L	B	M	D	H
15	1/2"	43	13	13	55	67.5
20	3/4"	45	14	14	55	69
25	1"	50	15	14	55	77
32	1 1/4"	57	21	17	60	84
40	1 1/2"	71	26	24	70	85
50	2"	78	32	27	70	105
65	2 1/2"	90	38	31	85	138
80	3"					
100	4"					

Technical Standard
 1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

MI-1203 Brass Flexible Gate Valve 黄铜伸缩闸阀



DN	Size	L	B	M	D	H
15	15x1/2"F	74-82	14	12.5	65	55
20	15X3/4"F	74-82	14	12.5	65	55
25	20 X 1"F	78-96	17	14.5	78	55
32	20X3/4"F	78-96	17	14.5	78	55
40	1 1/2"					
50	2"					
65	2 1/2"					
80	3"					
100	4"					

Technical Standard
 1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

MI-1303 Brass Quick Opening Gate Valve 黄铜快开闸阀



DN	Size	L	B	M	D	H
15	1/2"					
20	3/4"					
25	1"					
32	1 1/4"					
40	1 1/2"					
50	2"					
65	2 1/2"					
80	3"					
100	4"					

Technical Standard
 1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1204 Brass Gate Valve 黄铜磁性闸阀



DN	Size	L	B	M	H
15	1/2"	42	13	13	52
20	3/4"	50.5	17	15	63
25	1"	51	21	14	71
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-1304 Brass Compressed Gate Valve 黄铜卡套闸阀



DN	Size	L	B	M	D	H
15	1/2"	63	13	14	60.5	
20	3/4"	66	18	13	67	
25	1"	75	24	15	75	
32	1 1/4"					
40	1 1/2"					
50	2"					
65	2 1/2"					
80	3"					
100	4"					

Technical Standard
 1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228



优质黄铜
High Quality
Brass



成熟工艺
Mature
Technology



国家标准
Standard
Detection



超长使用
Extra Long
Use

球阀系列 BALL VALVE

ML-2001 Brass Ball Valve 黄铜球阀



DN	Size	L	L1	B	H	D	S
8	1/4"	45.8	11	11	46	72	21.5
10	3/8"	45.8	11	11	46	72	21.5
15	1/2"	49	11.5	14	48	87	24
20	3/4"	55.5	12.5	19	52.5	87	31
25	1"	64.5	14	23	58	104	37
32	1 1/4"	75	14	29	71	123	47
40	1 1/2"	83	16.5	37	76	123	52
50	2"	99	18.5	45	90	150	64.5
65	2 1/2"	120	21	57	100	225	80.5
80	3"	136	24.5	68	110	225	94
100	4"	156	23	85	127	225	122

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.: -20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2005 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	52.5	15	46	87.5
20	3/4"	60.5	20	49	87.5
25	1"	69.5	25	58	104
32	1 1/4"	78	32	69.5	136
40	1 1/2"	91	37	76.5	150
50	2"	104	47	84.5	150
65	2 1/2"	123	57	115	210
80	3"	155	68	132	210
100	4"	178	84	148	290

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.: -20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2002 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
8	1/4"				
10	3/8"				
15	1/2"	48	13.5	52	37
20	3/4"	57	18	52	41
25	1"	68	23	68	50
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.: -20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2006 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	59.5	15	46	68.5
20	3/4"	66.5	20	49	87.5
25	1"	76.5	25	58	104
32	1 1/4"	85	32	69.5	136
40	1 1/2"	100	37	76.5	150
50	2"	114.5	47	84.6	150
65	2 1/2"				
80	3"				
100	4"				

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.: -20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2003 Brass Ball Valve 黄铜球阀



DN	Size	L	L1	B	H	D
8	1/4"					
10	3/8"					
15	1/2"	52	37	56	13.5	
20	3/4"	52	41	65	18	
25	1"	68	50	77	23	
32	1 1/4"					
40	1 1/2"					
50	2"					
65	2 1/2"					
80	3"					
100	4"					

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.: -20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2007 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	52.5	15	42	50
20	3/4"	59	20	45.5	50
25	1"	69.5	25	56.5	62
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.: -20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2004 Brass Ball Valve 黄铜球阀



DN	Size	L	L1	B	H	D	S
15	1/2"	56	14	15	52	87	25.5
20	3/4"	61	15	19	55	87	30.5
25	1"	70	15	25	60	104	38
32	1 1/4"	75	16	29	71	123	46
40	1 1/2"	90	17	40	76	123	54
50	2"	107	20	50	90	150	67
65	2 1/2"						
80	3"						
100	4"						

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.: -20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2008 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	69	15	42	50
20	3/4"	79.5	20	45.5	50
25	1"	90	25	56.5	62
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.: -20°C ≤T≤150°C 4.Pipe Thread to ISO 228



卓越品质
High Quality
Brass



成熟工艺
Mature
Technology



国际权威
Standard
Detection



超长使用
Extra Long
Use

ML-2009 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	47	14	45	85
20	3/4"	55	19	48	85
25	1"	64	23	56	103
32	1 1/4"	75	30	70	120
40	1 1/2"	88	38	75	120
50	2"	100	47	87	150
65	2 1/2"	120	57	113	215
80	3"	148	69	130	215
100	4"	171	85	145	295

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2013 Brass Ball Valve 黄铜球阀



DN	Size	L	L1	B	H	D	S
15	1/2"	68	16	15	39.5	88	24
20	3/4"	76	18	19	45	88	29.5
25	1"	81	21	25	56	112	36.5
32	1 1/4"	104	23.5	32	62	120	45
40	1 1/2"	115	24	40	67	120	53
50	2"	135	28	50	83	126	65
65	2 1/2"						
80	3"						
100	4"						

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2010 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	58	14	45	85
20	3/4"	64	19	48	85
25	1"	78	23	56	103
32	1 1/4"	86	30	70	120
40	1 1/2"	101	38	75	120
50	2"	115	47	87	150
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2014 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	52.5	15	46	87.5
20	3/4"	60.5	20	49	87.5
25	1"	69.5	25	58	104
32	1 1/4"	78	32	69.5	136
40	1 1/2"	91	37	76.5	150
50	2"	104	47	84.5	150
65	2 1/2"	123	57	115	210
80	3"	155	68	132	210
100	4"	178	84	148	290

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2011 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	54	14	38	52
20	3/4"	59	19	42	52
25	1"	74	23	52	68
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2015 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	52	15	44.5	100
20	3/4"	63	19	47.5	100
25	1"	72	23	54	110
32	1 1/4"	75	30	72	137
40	1 1/2"	84.5	37	77	137
50	2"	93.5	42	91	165
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2012 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	54	14	38	52
20	3/4"	59	19	42	52
25	1"	74	23	52	68
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2016 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	60	15	50	101
20	3/4"	67	20	55	101
25	1"	84	24	60	125
32	1 1/4"	79	31	57	134
40	1 1/2"	97	40	66	139
50	2"	111	49	87	199
65	2 1/2"	142	62	118	169
80	3"	164	75	128	69
100	4"	185	90	139	169

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228



高品质黄铜
High Quality Brass



成熟工艺
Mature Technology



国家标准
Standard Detection



超长使用
Extra Long Use

ML-2017 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	43	12	40	86
20	3/4"	50	14.5	43	86
25	1"	59	19	46	110
32	1 1/4"	69	25	52	110
40	1 1/2"	78	29	60	140
50	2"	85	37	66	140
65	2 1/2"	118	50	96	230
80	3"	124	62	100	230
100	4"				

Technial Standard

1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2021 Brass Compressed Ball Valve 黄铜卡套球阀



DN	Size	L	B	H	D
15	1/2"	65	15	36	90
20	3/4"	80	22	40	90
25	1"	85	28	48	90
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technial Standard

1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2018 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	59	15	55	87
20	3/4"	70	21	59	87
25	1"	75	25	80	114
32	1 1/4"	87	31	98	148
40	1 1/2"	97	40	103	148
50	2"	109	49	108	182
65	2 1/2"	128	62	125	225
80	3"	146	79	138	225
100	4"	176	93	152	250

Technial Standard

1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2022 Brass Compressed Ball Valve 黄铜卡套球阀



DN	Size	L	B	H	D
15	1/2"				
20	3/4"				
25	1"				
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technial Standard

1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2019 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	58	15	49	102
20	3/4"	68	19	53	102
25	1"	80	25	58	130
32	1 1/4"	97	32	72	160
40	1 1/2"	109	40	78	160
50	2"	124	49	92	230
65	2 1/2"	143	62	118	320
80	3"	153	73	126	320
100	4"	184	90	139	320

Technial Standard

1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2023 Brass Compressed Ball Valve 黄铜卡套球阀



DN	Size	L	B	H	D
15	1/2"				
20	3/4"				
25	1"				
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technial Standard

1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2020 Welded Brass Ball Valve 黄铜焊接球阀



DN	Size	L	B	H	D
15	1/2"	64	12	40	87
20	3/4"	65	14	40	87
25	1"	73.5	19	45	105
32	1 1/4"	92	23	56	115
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technial Standard

1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2024 Brass Compressed Ball Valve 黄铜卡套球阀



DN	Size	L	B	H	D
15	1/2"				
20	3/4"				
25	1"				
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technial Standard

1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228



高品质黄铜
High Quality
Brass



成熟工艺
Mature
Technology



国家标准
Standard
Detection



超长使用
Extra Long
Use

ML-2025 Brass Mini Ball Valve 黄铜迷你球阀



DN	Size	L	B	H	D
15	1/2"	40	10	25	26
20	3/4"	40.5	10	26	26
25	1"	44	10	28	26
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2029 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	40	10	25	26
20	3/4"	40.5	10	26	26
25	1"	44	10	28	26
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2026 Brass Mini Ball Valve 黄铜迷你球阀



DN	Size	L	B	H	D
15	1/2"	45	8	28	20
20	3/4"	45	8	28	20
25	1"	45	10	30	20
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2030 Brass Temperature Ball Valve 黄铜测温球阀



DN	Size	L	B	H	D
15	1/2"	50	12	44.5	90
20	3/4"	57	14	48	90
25	1"	63	19	58	106
32	1 1/4"	79	25	61	106
40	1 1/2"	89	32	73	139
50	2"	99	39	79	139
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2027 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	57	15	43	85
20	3/4"	63	19	50	95
25	1"	69	24	58	106
32	1 1/4"	76	29	60	118
40	1 1/2"	85	35	68	134
50	2"	92	44	80	143
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2031 Brass Filter Valve 黄铜过滤器球阀



DN	Size	L	B	H	D
20	3/4"	98	17	47	99
25	1"	110	22	51.5	106

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2028 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	50	12	44.5	90
20	3/4"	57	14	48	90
25	1"	66	19	58	106
32	1 1/4"	76	25	61	106
40	1 1/2"	83	32	73	139
50	2"	90	39	79	139
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2032 PP-R Live-fit Brass Ball Valve PP-R 黄铜活接球阀



DN	Size	L	B	H	H
15	1/2"	89	14	41.5	47
20	3/4"	95.5	19	44.5	47
35	1"	108	22	49	47

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228



高品质黄铜
High Quality
Brass



成熟工艺
Mature
Technology



国家标准
Standard
Detection



超长使用
Extra Long
Use

ML-2033 Brass Lock ball valve 黄铜锁闭球阀



DN	Size	L	B	H	D
15	1/2"	50	13	36	126
20	3/4"	56	16	39	126
25	1"	65	20	45.5	126
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2037 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	98.5	15	55	54
20	3/4"				
25	1"				
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2034 Brass Filter Valve 黄铜过滤器球阀



DN	Size	L	B	H	D
15	1/2"	79	14	35	93
20	3/4"	88	17	38	93
25	1"	95	21	45	109
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2038 Brass Aluminum-Plastic Pipe Ball Valve 黄铜铝塑管球阀



DN	Size	L	B	H	D
15	1/2"	69	8	41.5	84.5
20	3/4"	70.5	12	42.5	84.5
25	1"				
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2035 Brass Filter Valve 黄铜过滤器球阀



DN	Size	L	B	H	D
15	1/2"	79	14.5	45	31
20	3/4"	88	17	48.2	31
25	1"	94.5	21	52	31
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2039 PP-R Brass Ball Valve PP-R 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	63	13.5	42	84.5
20	3/4"	70.5	17	45.5	92
25	1"	84	22.5	56.5	104.5
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2036 Brass Flexible Ball Valve 黄铜伸缩球阀



DN	Size	L	B	H	D
15	1/2"				
20	3/4"	71.5	15	43.5	43.5
25	1"				
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2040 PP-R Brass Ball Valve PP-R 黄铜球阀



DN	Size	L	B	H	D
	25 X 1"	118	23	52	80
	32 X 1"	122	23	52	80

Technical Standard
 1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228



球阀系列 BALL VALVE

ML-2101 Brass Double Articulated Ball Valve 黄铜双活接球阀



DN	Size	L	B	H	D
15	20x20	72	12	42	80
20	25x25	80	17	47	90
25	32x32	94	23	49	92
32	40x40	101	24	57	117
40	50x50	116	28	70	117
50	63x63	137	36	104	133
65	75x75	165	47	100	185
80					
100					

Technial Standard
 1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2105 Brass Gas Valve 黄铜燃气球阀



DN	Size	L	B	H	D
15	1/2"	57	15	43	85
20	3/4"	63	19	50	95
25	1"	69	24	58	106
32	1 1/4"	76	29	60	118
40	1 1/2"	85	35	68	134
50	2"	92	44	80	143
65	2 1/2"				
80	3"				
100	4"				

Technial Standard
 1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2102 PP-R Brass Ball Valve PP-R 黄铜外丝球阀



DN	Size	L	B	H	D
15	1/2X20"	70	13.5	42	84.5
20	3/4X25"	75.5	17	45.5	92
25	32 X 1"	91.5	22.5	56.5	104.5
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technial Standard
 1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2106 Brass Ball Valve 黄铜球阀



DN	Size	L	B	H	D
15	1/2"	55	15	69	52.5
20	3/4"	69	20	82	52.5
25	1"				
32	1 1/4"				
40	1 1/2"				
50	2"				
65	2 1/2"				
80	3"				
100	4"				

Technial Standard
 1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2103 Multifunction Brass Ball Valve 多功能黄铜球阀



DN	Size	L	B	H	D
15	1"X 25	165	23	55	90
20	1"X 32	170	23	55	100
25					
32					
40					
50					
65					
80					
100					

Technial Standard
 1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2107 Brass Mini Ball Valve 黄铜迷你球阀



DN	Size	L	B	H	D
8	1/4"	41	6	32	26
10	3/8"	41	8	32	26
15	1/2"	43	10	32	26

Technial Standard
 1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2104 Multifunction Brass Ball Valve 多功能带表黄铜球阀



CODE	Size	L	B	H	D
15101	1"X25	152	19	50	67
15102	1"X32	160	19	50	67

Technial Standard
 1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-2108 Brass Drain Valve 黄铜排污阀



DN	Size	L	B	H	D
8	1/4"				
10	3/8"	66	9	31	23.5
15	1/2"	66	9	31	23.5

Technial Standard
 1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
 3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228



高品质黄铜
High Quality Brass



成熟工艺
Mature Technology



国家标准
Standard Detection



超长使用
Extra Long Use

水嘴系列 BIBCOCK

ML-3005 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	90	10	80	87
20	3/4"X1"	100	12.5	86	87
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3006 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	85	10	80	87
20	3/4"X1"	96	12.5	86	87
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3007 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	87	85	82	13
20	3/4"X1"	91	86	87	13

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3008 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	104.5	95.5	97	10

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3009 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	88	10	80	87
20	3/4"X1"	98	12.5	86	87
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3010 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	87	13	85	82
20	3/4"X1"	91	13	86	87
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3011 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	87	13	85	82
20	3/4"X1"	91	13	86	87
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3012 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	88	10	80	50
20	3/4"X1"	98	12.5	86	50
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228



优质黄铜
High Quality
Brass



成熟工艺
Mature
Technology



国家标准
Standard
Detection



超长使用
Extra Long
Use

水嘴系列 BIBCOCK

ML-3013 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	88	10	80	87
20	3/4"X1"	98	12.5	86	87
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3017 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	95	7	110	41
20	3/4"X1"				
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3014 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	88	10	80	87
20	3/4"X1"	98	12.5	86	87
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3018 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"		15	104	55
20	3/4"X1"		18	108	55
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3015 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	88.5	15	119	45
20	3/4"X1"				

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3019 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	91.5	15	76.5	60
20	3/4"X1"	95	15	80	60
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3016 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	95	7	110	41

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3020 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	73.5	14.5	59	60
20	3/4"X1"	76	15	59	60
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228



特选黄铜
High Quality
Brass



成熟工艺
Mature
Technology



国家标准
Standard
Detection



超长使用
Extra Long
Use

水嘴系列 BIBCOCK

ML-3101 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	95	7	110	41
20	3/4"X1"	97	7	110	41
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3105 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	57	8	42	51.5
20	3/4"X1"				
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3102 Zinc Alloy Bibcock 锌合金水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	15			
20	3/4"X1"				
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3106 Zinc Alloy Bibcock 锌合金水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"				
20	3/4"X1"				
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3103 Zinc Alloy Bibcock 锌合金水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"				
20	3/4"X1"				

Technial Standard

1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3107 Zinc Alloy Bibcock 锌合金水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	100	14.5	80	50
20	3/4"X1"				
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3104 Zinc Alloy Bibcock With Lock 锌合金带锁水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"				
20	3/4"X1"				

Technial Standard

1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-3108 Brass Bibcock 黄铜水嘴



DN	Size	L	B	H	D
15	1/2"X3/4"	95	13.5	86	
20	3/4"X1"				
25	1"X1-1/4"				

Technial Standard

1.Nominal pressure:PNs1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228



优质黄铜
High Quality
Brass



成熟工艺
Mature
Technology



国家标准
Standard
Detection



超长使用
Extra Long
Use

角阀系列 ANGLE VALVE

ML-4005 Brass Angle Valve 黄铜角阀



DN	Size	L	H	C	B
15	3/8"X1/2"				
15	1/2"X1/2"				

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-4009 Brass Angle Valve 黄铜角阀



DN	Size	L	H	C	B
15	3/8"X1/2"				
15	1/2"X1/2"				
15					

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-4006 Brass Angle Valve 黄铜角阀



DN	Size	L	H	C	B
15	3/8"X1/2"				
15	1/2"X1/2"				

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-4010 Brass Angle Valve 黄铜角阀



DN	Size	L	H	C	B
15	3/8"X1/2"	50.5	45.5		16
15	1/2"X1/2"				
15	1/2"X3/4"				

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-4007 Brass Angle Valve 黄铜角阀



DN	Size	L	H	C	B
15	3/8"X1/2"	27	76	35	7
15	1/2"X1/2"	27	76	35	7
15	1/2"X3/4"	30	81	40	9

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-4011 Brass Angle Valve 黄铜角阀



DN	Size	L	H	C	B
15	3/8"X1/2"				
15	1/2"X1/2"				
15	1/2"X3/4"				

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-4008 Brass Angle Valve 黄铜角阀



DN	Size	L	H	C	B
15	3/8"X1/2"	27	76	35	7
15	1/2"X1/2"	27	76	35	7
15	1/2"X3/4"	30	81	40	9

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-4012 Brass Angle Valve 黄铜角阀



DN	Size	L	H	C	B
15	3/8"X1/2"				
15	1/2"X1/2"				

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228



卓越品质
High Quality
Brass



成熟工艺
Mature
Technology



国家标准
Standard
Detection



超长使用
Extra Long
Use

角阀系列 ANGLE VALVE

ML-4013 Brass Angle Valve 黄铜角阀



DN	Size	L	H	C	B
15	3/8"X1/2"				
15	1/2"X1/2"				

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-4014 Brass Angle Valve 黄铜角阀



DN	Size	L	H	C	B
15	3/8"X1/2"				
15	1/2"X1/2"				

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-4015 Brass Angle Valve 黄铜角阀



DN	Size	L	H	C	B
15	3/8"X1/2"				
15	1/2"X1/2"				
15	1/2"X3/4"				

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-4016 Brass Angle Valve 黄铜角阀



DN	Size	L	H	C	B
15	3/8"X1/2"				
15	1/2"X1/2"				
15	1/2"X3/4"				

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-4017 Brass Angle Valve 黄铜角阀



DN	Size	L	H	C	B
15	3/8"X1/2"	43	60	26	10
15	1/2"X1/2"	45	60	26	10
15	1/2"X3/4"	45	68	30.5	10

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-4018 Brass Angle Valve 黄铜角阀



DN	Size	L	H	C	B
15	3/8"X1/2"	60.5	57.5	46	8
15	1/2"X1/2"	60.5	57.5	46	8
15	1/2"X3/4"				

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-4019 Brass Angle Valve 黄铜角阀



DN	Size	L	H	C	B
15	3/8"X1/2"				
15	1/2"X1/2"				
15	1/2"X3/4"				

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:-20°C ≤T≤150°C 4.Pipe Thread to ISO 228



卓越品质
High Quality
Brass



成熟工艺
Mature
Technology



国际标准
Standard
Detection



超长使用
Extra Long
Use

截止阀系列 STOP VALVE

ML-5001 Brass Stop Valve 黄铜截止阀



DN	Size	L	B	M	D	H
15	1/2"	46	12.5	12	55	55
20	3/4"	50.5	13	11	60	60
25	1"	62.5	17	14.5	70	70
32	1 1/4"	70	22	14	80	80
40	1 1/2"	82	35	17	100	100
50	2"	92	39	19	100	100
65	2 1/2"					
80	3"					
100	4"					

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-5004 Brass Stop Valve 黄铜截止阀



DN	Size	L	B	M	D	H
15	1/2"					
20	3/4"					
25	1"					
32	1 1/4"					
40	1 1/2"					
50	2"					
65	2 1/2"					
80	3"					
100	4"					

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-5002 Brass Stop Valve 黄铜截止阀



DN	Size	L	B	M	D	H
15	1/2"	46	13	10.5	53	75
20	3/4"					
25	1"					
32	1 1/4"					
40	1 1/2"					
50	2"					
65	2 1/2"					
80	3"					
100	4"					

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-5005 Brass Stop Valve 黄铜截止阀



DN	Size	L	B	M	D	H
15	1/2"	46	13	10.5	53	75
20	3/4"					
25	1"					
32	1 1/4"					
40	1 1/2"					
50	2"					
65	2 1/2"					
80	3"					
100	4"					

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-5003 Brass Stop Valve 黄铜截止阀



DN	Size	L	B	M	D	H
15	1/2"	46	13	10.5	53	75
20	3/4"					
25	1"					
32	1 1/4"					
40	1 1/2"					
50	2"					
65	2 1/2"					
80	3"					
100	4"					

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-5006 Brass Stop Valve 黄铜截止阀



DN	Size	L	B	M	D	H
40	1-1/2"	40	78.5	154.5	100	30.5
50	2"	50	80.5	154.5	100	44.5
65	2-1/2"	65	95.5	182.5	100	63

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228



高品质黄铜
High Quality
Brass



成熟工艺
Mature
Technology



国家标准
Standard
Detection



超长使用
Extra Long
Use

ML-7101 Brass Release Valve 黄铜排气阀



DN	Size	H	S
10	1/4	16	71
12	3/8	20	71
15	1/2	22	71
20	3/4	27	76
25	1"	33	76

Technial Standard

- 1.Nominal pressure:PN≤1.6Mpa
- 2.Working Medium:Water
- 3.Working Temp.:20°C ≤T≤120°C
- 4.Pipe Thread to ISO 228

ML-7102 Brass Release Valve 黄铜排气阀



DN	Size	H	S
10	1/4	16	71
12	3/8	20	71
15	1/2	22	71
20	3/4	27	76
25	1"	33	76

Technial Standard

- 1.Nominal pressure:PN≤1.6Mpa
- 2.Working Medium:Water
- 3.Working Temp.:20°C ≤T≤120°C
- 4.Pipe Thread to ISO 228

ML-7103 Brass Release Valve 黄铜排气阀



DN	Size	H	S
15	1/2	71	22
20	3/4	76	27

Technial Standard

- 1.Nominal pressure:PN≤1.6Mpa
- 2.Working Medium:Water
- 3.Working Temp.:20°C ≤T≤120°C
- 4.Pipe Thread to ISO 228

ML-7104 Brass Release Valve 黄铜排气阀



DN	Size	H	S
10	1/4	16	71
12	3/8	20	71
15	1/2	22	71
20	3/4	27	76
25	1"	33	76

Technial Standard

- 1.Nominal pressure:PN≤1.6Mpa
- 2.Working Medium:Water
- 3.Working Temp.:20°C ≤T≤120°C
- 4.Pipe Thread to ISO 228

ML-7105 Brass Three Tailpiece 黄铜三尾件



DN	Size	L	H	C	B
15	3/8"X1/2"				

Technial Standard

- 1.Nominal pressure:PN≤1.6Mpa
- 2.Working Medium:Water/Non-corrosive liquid
- 3.Working Temp.:20°C ≤T≤150°C
- 4.Pipe Thread to ISO 228

ML-7106 Electric Valve 电动球阀

概述

电动球阀是专供中央空调盘管的配套产品，由驱动器与阀体两部分组成，驱动器由一个同步电机驱动，具备弹簧复位及手动开阀杠杆操纵功能。工作原理是驱动器由可逆同步马达驱动，并带磁性离合器。利用马达通过马达转子与离合器所产生的磁性作用，能在停顿的情况下产生稳定的扭力。故此当马达设有电流通过时能稳定地停顿在任何一点，当阀门全开或全关时磁离合器分离，停止调节。驱动器的递增式或比例式控制器所发讯号能使马达顺时针转动或逆时针转动。

技术原理

电动球阀由温度传感器，比例积分温度控制器和电动调节阀组成送风温度控制系统，安装在送风管道的温度传感器，把检测到的温度信号传至温度控制器，由温度控制器将温度传感器的检测值与设定值不断比较，同时不断地输出信号，控制电动调节阀的开度连接可调，最终使温度传感器测量的环境温度保持在设定的温度范围内。



主要材质

阀体: Hpb59-1 阀座: PTFE O型圈: FKM 阀盖: Hpb59-1 阀杆: Hpb59-1 球体: SUS304/Hpb59-1



卓越品质
High Quality
Brass



成熟工艺
Mature
Technology



国际权威
Standard
Detection



超长使用
Extra Long
Use



止回阀系列 CHECK VALVE



DN	Size	L	B	H
15	1/2"	47	14	32
20	3/4"	56	17	35
25	1"	65	22	45
32	1 1/4"	70	30	50
40	1 1/2"	78	35	58
50	2"	88	45	68
65	2 1/2"			
80	3"			
100	4"			

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.: -20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-8102 Brass Check Valve 黄铜止回阀 (卧式)



DN	Size	L	B	H
15	1/2"	47.5	14	35.5
20	3/4"	56	18	39
25	1"	63	22	46.5
32	1 1/4"	71	28	51
40	1 1/2"	80.5	33.5	59.5
50	2"	93	43	67
65	2 1/2"	105	48.5	77
80	3"	123	64	81
100	4"	162	83	101

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.: -20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-8103 Brass Check Valve 黄铜止回阀 (立式)



DN	Size	L	B	H	D
15	1/2"	45.5	36		18
20	3/4"	52	42		23
25	1"	57.5	47		29
32	1 1/4"	62.5	59.5		36
40	1 1/2"	71	66.5		42.5
50	2"	78.5	83		53.5
65	2 1/2"	93	95		66
80	3"	100	110		79
100	4"	112	143		99

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.: -20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-8104 Brass Check Valve 黄铜止回阀 (立式)



DN	Size	L	B	H	D
15	1/2"	58	36		18
20	3/4"	65	42		23
25	1"	74.5	47		29
32	1 1/4"	82	59.5		36
40	1 1/2"	91	66.5		42.5
50	2"	100	83		53.5

Technical Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.: -20°C ≤T≤150°C 4.Pipe Thread to ISO 228



卓越品质
High Quality
Brass



成熟工艺
Mature
Technology



国家标准
Standard
Detection



超长使用
Extra Long
Use

ML-8105 Brass Check Valve 黄铜止回阀 (立式)



DN	Size	L	B	H	D
15	1/2"	51	33		20
20	3/4"	54	38		21
25	1"	62.5	47.5		27.5

Technical Standard

- 1.Nominal pressure:PN≤1.6Mpa
- 2.Working Medium:Water/Non-corrosive liquid
- 3.Working Temp.:20°C ≤T≤150°C
- 4.Pipe Thread to ISO 228

ML-8201 Brass Foot Valve 黄铜底阀



DN	Size	L	B	D
25	1"	80.5	51	31
32	1 1/4"	93	60.5	36.5
40	1 1/2"	100	68.5	44
50	2"	117	80	55.5
65	2 1/2"	137.5	100	68
80	3"	174.5	121	81

Technical Standard

- 1.Nominal pressure:PN≤1.6Mpa
- 2.Working Medium:Water/Non-corrosive liquid
- 3.Working Temp.:20°C ≤T≤150°C
- 4.Pipe Thread to ISO 228

ML-8106 Brass Check Valve With Strainer 黄铜带网止回阀 (立式)



DN	Size	L	B	D
20	3/4"	89.5	42	20
25	1"	100	46.5	25
32	1 1/4"	112	59	32
40	1 1/2"	129	67	40
50	2"	150.5	82	50

Technical Standard

- 1.Nominal pressure:PN≤1.6Mpa
- 2.Working Medium:Water/Non-corrosive liquid
- 3.Working Temp.:20°C ≤T≤150°C
- 4.Pipe Thread to ISO 228

ML-8202 Brass Filter 黄铜过滤器 (Y型)



DN	Size	L	B	D
15	1/4"	54.5	33.5	13
20	1/2"	55.5	33.5	15
25	3/4"	68	39.5	20
32	1"	71.5	44.5	23
40	1 1/4"	96	55	30
50	1 1/2"	105	65.5	34
65	2"	125	73	16

Technical Standard

- 1.Nominal pressure:PN≤1.6Mpa
- 2.Working Medium:Water/Non-corrosive liquid
- 3.Working Temp.:20°C ≤T≤150°C
- 4.Pipe Thread to ISO 228

ML-8107 Brass Check Valve With Strainer 黄铜带网止回阀 (立式)



DN	Size	L	B	H	D
15	1/2"	84	33		18
20	3/4"	88	38		23
25	1"	104	47.5		29
32	1 1/4"	150	82.5		36
40	1 1/2"				42.5
50	2"				53.5
65					66
80					79
100					99

Technical Standard

- 1.Nominal pressure:PN≤1.6Mpa
- 2.Working Medium:Water/Non-corrosive liquid
- 3.Working Temp.:20°C ≤T≤150°C
- 4.Pipe Thread to ISO 228

ML-8203 Brass Check Valve 黄铜止回阀 (Y型)



DN	Size	L	B	H	D

Technical Standard

- 1.Nominal pressure:PN≤1.6Mpa
- 2.Working Medium:Water/Non-corrosive liquid
- 3.Working Temp.:20°C ≤T≤150°C
- 4.Pipe Thread to ISO 228

ML-8108 Brass Check Valve With Strainer 黄铜带网止回阀 (立式)



DN	Size	L	B	H	D
15	1/2"	77	33		20
20	3/4"	85	38		21
25	1"	97	47.5		27.5

Technical Standard

- 1.Nominal pressure:PN≤1.6Mpa
- 2.Working Medium:Water/Non-corrosive liquid
- 3.Working Temp.:20°C ≤T≤150°C
- 4.Pipe Thread to ISO 228

ML-8204 Brass Check Valve 黄铜止回阀 (Y型)



DN	Size	L	B	H	D
15	1/2"	60	13	41	
20	3/4"	71	16.5	47	
25	1"	88	23	57	
32	1 1/4"	95	28	67	
40	1 1/2"	102	35	73	
50	2"	128	50	96	
65	2 1/2"	150	58	120	
80	3"	189	68	145	

Technical Standard

- 1.Nominal pressure:PN≤1.6Mpa
- 2.Working Medium:Water/Non-corrosive liquid
- 3.Working Temp.:20°C ≤T≤150°C
- 4.Pipe Thread to ISO 228



高品质黄铜
High Quality
Brass



成熟工艺
Mature
Technology



标准检测
Standard
Detection



超长使用
Extra Long
Use

浮球阀系列 FLOAT VALVE

ML-8301 Brass Float Valve 黄铜浮球阀



DN	Size	A	B	C	D
15	1/2"	74		265	4
20	3/4"	81		322	6.5
25	1"	92		356	9.5
32	1 1/4"	104.5		392	12
40	1 1/2"	111		415	17
50	2"	123		445	20

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-8304 Brass Float Valve 黄铜浮球阀



DN	Size	A	B	C	D
		74		265	4
		81		322	6.5
		92		356	9.5
		104.5		392	12
		111		415	17
		123		445	20

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-8302 Brass Float Valve 黄铜浮球阀



DN	Size	A	B	C	D
15	1/2"	74		265	4
20	3/4"	81		322	6.5
25	1"	92		356	9.5
32	1 1/4"	104.5		392	12
40	1 1/2"	111		415	17
50	2"	123		445	20

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-8305 Brass Float Valve 黄铜浮球阀



DN	Size	A	B	C	D
15	1/2"	67.5		240	8
20	3/4"	70.5		308.5	8
25	1"	83		314.5	12.5

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-8303 Brass Float Valve 黄铜浮球阀



DN	Size	A	B	C	D
15	1/2"	74		265	4
20	3/4"	81		322	6.5
25	1"	92		356	9.5
32	1 1/4"	104.5		392	12
40	1 1/2"	111		415	17
50	2"	123		445	20

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228

ML-8306 Brass Float Valve 黄铜浮球阀



DN	Size	A	B	C	D
15	1/2"	64.5		204	8.5
20	3/4"	67		216.5	10
25	1"	81		289.5	12.5

Technial Standard

1.Nominal pressure:PN≤1.6Mpa 2.Working Medium:Water/Non-corrosive liquid
3.Working Temp.:20°C ≤T≤150°C 4.Pipe Thread to ISO 228



高品质黄铜
High Quality
Brass



成熟工艺
Mature
Technology



国家标准
Standard
Detection



超长使用
Extra Long
Use

波纹管系列
BELLOWS

ML-9201 Stainless Steel Air Bellows (Copper Connector)
不锈钢空调波纹管 (铜接头)



ML-9301 Gas Pipe 燃气管



ML-9202 Stainless Steel Air Bellows (Copper Connector)
不锈钢空调波纹管 (铜接头)



ML-9302 Gas Pipe 燃气管



ML-9203 Stainless Steel Air Bellows (Copper Connector)
不锈钢空调波纹管 (铜接头)



ML-9303 Gas Pipe 燃气管



管件系列
PIPE FITTINGS

ML-9101



ML-9105



ML-9102



ML-9106



ML-9103



ML-9107



ML-9104



ML-9108



卓越品质
High Quality
Brass



成熟工艺
Mature
Technology



国际标准
Standard
Detection



超长使用
Extra Long
Use

Алматы (7273)495-231
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Россия (495)268-04-70

Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Казахстан (7172)727-132

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

По вопросам продаж и поддержки обращайтесь: